

Tigerply TigerLINE Okoume Plywood

2700x1200x9mm

BPIR Declaration

Version: v1

Designated building product: Class 1

Declaration

Keyland Investments Ltd has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

| | |
|------------|---|
| Name | Tigerply TigerLINE Okoume Plywood 2700x1200x9mm |
| Line | Untreated poplar core |
| Identifier | TPOK092712 |

Description

Non-Structural FSC Okoume veneer plywood manufactured on a plantation polar core. A 'B' grade face veneer. Manufactured using E-Zero, Type II, Water resistant interior glue lines which are CARB2 Certified. Sheet size is 2700mm x 1200mm, 9mm thick +/- 0.5mm Suitable for interior use only

Scope of use

An interior lining plywood which can be used on interior walls and ceilings. Has a high impact resistance making it suitable for use in areas such as garages, sheds and commercial buildings.

Not intended to provide structural bracing to the building. Not suitable for use in wet areas such as bathrooms and laundries. Not suitable for use in food preparation areas such as kitchens. Not acoustically rated, and may not be suitable to form part of an intertenancy wall. Not suitable for use in areas of buildings where there are

building code obligations under C3.4 (a) Not rated as part of a fire protected boundary or fire wall. Not suitable for use adjacent to combustion appliances such as fire places or gas hobs.

Conditions of use

Suitable for interior use under normal humidity conditions. Not suitable for use in wet or high humidity areas. Not for exterior use.

Relevant building code clauses

B1 Structure – B1.3.1, B1.3.2, B1.3.3 (j), B1.3.4

F2 Hazardous building materials – F2.3.1

Contributions to compliance

Supporting documentation

The following additional documentation supports the above statements:

None added

For further information supporting Tigerply TigerLINE Okoume Plywood 2700x1200x9mm claims refer to our website.

Contact details

| | |
|--|----------------------------------|
| Manufacture location | Overseas |
| Legal and trading name of manufacturer | Shelter Forest International Ltd |

| | |
|------------------------------------|--|
| Legal and trading name of importer | Keyland Investments Ltd |
| Importer address for service | 334D Te Ngae Road Rotorua 3010 |
| Importer website | www.keyland.co.nz |
| Importer NZBN | 9429033062440 |
| Importer email | sales@keyland.co.nz |
| Importer phone number | 0800113171 |

Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that Tigerply TigerLINE Okoume Plywood 2700x1200x9mm is not subject to a warning on ban under [s26 of the Building Act](#).

On behalf of **Keyland Investments Ltd**:

Euan Rutherford

BUSINESS UNIT MANAGER

December, 2023

KEYLAND INVESTMENTS LTD
334D Te Ngae Road Rotorua 3010 New Zealand
[0800113171](tel:0800113171) | www.keyland.co.nz

Appendix

Note: The below appendix includes information relating to BPIR Ready.

Publishing this information is not a requirement under BPIR. Its inclusion here is to provide a reference for how this BPIR summary was generated as well as to help summary creators understand the performance clauses suggested by BPIR Ready.

BPIR Ready selections

Category: Internal linings

| | Yes | No |
|--|-----|----|
| Use to provide structural bracing | | ✗ |
| Use in wet areas | | ✗ |
| Use in food preparation areas | | ✗ |
| Part of an intertenancy / abutting occupancy wall system | | ✗ |
| Use in areas with surface fire obligations | | ✗ |
| Part of a fire protected boundary or fire wall | | ✗ |
| Use in areas with near to sources of heat | | ✗ |

Building code performance clauses

B1 Structure

B1.3.1

Buildings, building elements and sitework shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during *construction* or *alteration* and throughout their lives.

B1.3.2

Buildings, building elements and sitework shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during *construction* or *alteration* when the *building* is in use.

B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of *buildings, building elements* and *sitework*, including:

- (j) impact

B1.3.4

Due allowances shall be made for:

- a. the consequences of failure,
- b. the intended use of the *building*,
- c. effects of uncertainties resulting from *construction* activities, or the sequence in which *construction* activities occur,
- d. variation in the properties of materials and the characteristics of the site, and
- e. accuracy limitations inherent in the methods used to predict the stability of *buildings*

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.